



DXL603

SPECIFICATIONS

| | |
|---|--|
| <p>Computerised Sewing Machine</p> <p>Aluminium Diecast Body</p> <p>Free Arm / Flat Bed Conversion</p> <p>Machine Size: 406 x 298 x 184mm</p> <p>Built in Stitches: 60 (<i>Incl. 6 Buttonholes</i>)</p> <p>Maximum Sewing Speed: 820 s.p.m.</p> <p>Superior Feed System (SFS) / 7 Piece Feed Dog</p> <p>Foot Pressure Adjustment (<i>6 Levels</i>)</p> <p>Maximum Stitch Length: 5mm</p> <p>LED Lamp</p> <p>Start / Stop Button with Slow Stop/Start Function</p> <p>Manual Thread Tension Control</p> <p>Drop Feed</p> <p>Power Switch</p> <p>Extra Needle Penetration Power</p> <p>Twin Needle Facility</p> <p>Carry Handle</p> | <p>Horizontal Full Rotary Hook</p> <p>Top Loading - Category B</p> <p>Arm Space: 170mm</p> <p>Approximate Weight: 5.6kg</p> <p>LCD Display</p> <p>Needle Threader</p> <p>Maximum Stitch Width: 7mm</p> <p>Horizontal Type Spool Pin</p> <p>Needle Up / Down</p> <p>Reverse Button</p> <p>Speed Control Slider</p> <p>Auto De Clutch Bobbin Winder</p> <p>Auto Lock Stitch</p> <p>Snap on Feet</p> <p>Reverse Key</p> <p>Hard Cover</p> <p>Origin: Taiwan</p> |
|---|--|

STANDARD ACCESSORIES

| | |
|--|---|
| <p>Automatic Buttonhole Foot</p> <p>Blind Hem Foot</p> <p>Overedge Foot</p> <p>Lint Brush</p> <p>Satin Stitch Foot</p> <p>Screwdriver (3 Pronged)</p> <p>Seam Ripper</p> <p>Spool Cap (Large)</p> <p>Spool Cap (Small)</p> | <p>Spool Pin (Spare)</p> <p>Spool Pin Felt</p> <p>Spool Stand</p> <p>Standard Foot (Black Button)</p> <p>Zipper Foot</p> <p>Bobbins x 4 (Plastic)</p> <p>Needles</p> <p>Foot Control</p> <p>Power Cable</p> |
|--|---|